

Coating for Metal, FRP

METALKING

Features

- Restore the slight wound which was possible on the matrix surface.
- Fine weather ability enables prevention from weathering, deteriorating.
- Hardness of the coating after the drying is 3~4H by the pencil hardness.

Applications

- Protection and Prevention for metal, FRP from stains and dirt.

Directions

1. Make sure surface is clean, dry and free of waxes and coatings.
2. Mask off baseboards and adjacent areas to avoid apply onto surfaces not intended to be treated.
3. Use a flat mop, handy mop, paint pad, roller or brush to apply. Better results will be obtained using a mop, pad, roller or brush. **DO NOT USE A SPRAYER.** Sprayers increase exposure hazard.
4. Full cure is achieved after 24 hours.
5. Rags and equipment that are wet with product may be combustible. Clean up promptly after job is complete. Clean equipment with mineral spirits and allow to dry in a well-ventilated area. Allow rags to dry in a well-ventilated area out of the reach of children and pets. When dry, dispose of in accordance with local waste disposal regulations.

Coverage: 10~30 m²/ℓ

Caution

1. **METALKING** is inflammable. Read MSDS carefully and ensure that the area is well-ventilated during application and until the surface is dry to the touch. Keep children and pets out of the area until foot traffic resumes.
2. Make sure **METALKING** is suitable for your specific purpose conditions and applications before use. Always test in a small inconspicuous area.
3. **DO NOT USE A SPRAYER.** Sprayers increase exposure hazard.
4. Use **METALKING** as it is. Don't mix neither water/any kind of solvent nor impurities.

5. Do not apply **METALKING** under this conditions such as
 - The surface is wet. ●During the rainy season ●Humidity is extremely high
 - Surface temperature above 40°C. ●Surface temperature below 10°C.
6. Full cure is achieved after 24 hours; foot traffic may begin in 4-5 hours.
7. Store **METALKING** in a sealed container, in a cool place(30°C or below), keep out of the reach of children.
8. Be careful not to spill **ARISTON** when pounding from storage container.
9. Avoid touching the skin as much as possible when using **METALKING**. Wear the box respirator, the eye shield, the protective glove, and the apron, etc. when you work.
10. Please use **METALKING** as early as possible after opening a letter.
11. Wash your hand and gargle enough after it uses it.
12. Do not use **METALKING** for any other purposes.

Properties

Appearance: Clear and transparent

Ingredient: Silicone Mixture

Available Sizes: 4 Liter & 16 Liter

Usage: Flammable

Storage conditions: Use within one year from when sealed off and stored below 30°C

*Complies with the Japanese Food Sanitation Law.

* **METALKING** does not use raw materials containing formaldehyde at all.

* For improvement of a product, there is a case to change contents without a notice.